

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	1425	1524		
	kW	1140	1219		
Prime Power (PRP)	kVA	1293	1368		
	kW	1035	1094		



Engine					
Manufacturer		MITSUBISHI			
Origin		JAPAN			
Model		S12R-PTA			
No of Cylinder / Configuration		12 - V TYPE			
Displacement		lt	49,03		
Bore / Stroke		mm	170 / 180		
Compression Ratio		14:1			
Aspiration		Turbocharged and Aftercooled			
Governor Type		ELECTRONIC			
Cooling System		WATER			
Coolant Capacity		lt	300		
Lubrication Oil Capacity		lt	180		
Electrical System		VDC	24		
Speed / Frequency			1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power		kWm	1220	1320	
Fuel Consumption	lt/h	110 %	300	330	
		100 %	271	298	
		75 %	208	229	
		50 %	151	166	
Exhaust Outlet Temperature		°C	492	TBD	
Exhaust Gas Flow		m³/min	258	287	
Combustion Air Flow		m³/min	98	109	
Cooling Air Flow		m³/min	1800	1800	

Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator					
Manufacturer		MARELLI			
Origin		ITALY			
Model		MJB400LB4			
No of Phase		3			
Power Factor		0,8			
No of Bearing		SINGLE			
No of Poles		4			
No of Leads		6			
Voltage Regulation (Steady State)		± %0,5			
Insulation Class		H			
Degree of Protection		IP 23			
Excitation System		AVR (Automatic Voltage Regulator), Brushless			
Connection Type		STAR			
Total Harmonic Content (No Load)		< %2			
Frequency		Hz	50	60	
Voltage Output		VAC	230 / 400	254 / 440	
Rated Power (Standby)		kVA	1430	1670	
Efficiency		%	95,8	96	

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	2468 x 6078 x 3750	14780	1470	TBA
Open Skid	2000 x 4500 x 2390	9510	1470	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask TBD: To Be Determined NA: Not Available N/A: Not Applicable

TTD1425MS0508-EN

www.teksangenerator.com

