

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	204	227		
	kW	163	182		
Prime Power (PRP)	kVA	184	205		
	kW	147	164		

**TBA**

Engine					
Manufacturer		PERKINS			
Origin		U.K.			
Model		1106C-E66TAG4			
No of Cylinder / Configuration		6 - INLINE			
Displacement		lt	6,6		
Bore / Stroke		mm	105 / 127		
Compression Ratio		16,2:1			
Aspiration		Turbocharged and Air-to-Air Charged Cooled			
Governor Type		ELECTRONIC/ECM			
Cooling System		WATER			
Coolant Capacity		lt	21		
Lubrication Oil Capacity		lt	16,5		
Electrical System		VDC	12		
Speed / Frequency			1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power		kWm	180,4	204,3	
Fuel Consumption	lt/h	110 %	43,8	50,4	
		100 %	40,2	41,3	
		75 %	31	36,8	
		50 %	20,5	25,5	
Exhaust Outlet Temperature		°C	499	509	
Exhaust Gas Flow		m³/min	31	34,8	
Combustion Air Flow		m³/min	11,7	13,4	
Cooling Air Flow		m³/min	327,6	387	



### Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

### Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator					
Manufacturer		MARELLI			
Origin		ITALY			
Model		MJB250MB4			
No of Phase		3			
Power Factor		0,8			
No of Bearing		SINGLE			
No of Poles		4			
No of Leads		12			
Voltage Regulation ( Steady State)		± %0,5			
Insulation Class		H			
Degree of Protection		IP 23			
Excitation System		AVR (Automatic Voltage Regulator), Brushless			
Connection Type		STAR			
Total Harmonic Content (No Load)		< %2			
Frequency		Hz	50	60	
Voltage Output		VAC	230 / 400	254 / 440	
Rated Power (Standby)		kVA	205	235	
Efficiency		%	93	92,6	

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	1037 x 3265 x 1700	2032	168	TBA
Open Skid	750 x 2400 x 1520	1612	144	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.  
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.  
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask    TBD: To Be Determined    NA: Not Available    N/A: Not Applicable

TTD205PE0309-EN

www.teksangenerator.com

