

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	330	385		
	kW	264	308		
Prime Power (PRP)	kVA	300	346		
	kW	240	276		



Engine				
Manufacturer		DOOSAN		
Origin		KOREA		
Model		P126TI-II		
No of Cylinder / Configuration		6 - INLINE		
Displacement	lt	11,1		
Bore / Stroke	mm	123 / 155		
Compression Ratio		17:1		
Aspiration		Turbocharged and Intercooled		
Governor Type		ELECTRONIC		
Cooling System		WATER		
Coolant Capacity	lt	65		
Lubrication Oil Capacity	lt	23		
Electrical System	VDC	24		
Speed / Frequency		1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power	kWm	294	342	
Fuel Consumption	lt/h	110 %	77,6	89,5
		100 %	63,1	73,8
		75 %	47	56
		50 %	31,3	37
Exhaust Outlet Temperature	°C	590	580	
Exhaust Gas Flow	m³/min	47,4	64,2	
Combustion Air Flow	m³/min	20,1	28,2	
Cooling Air Flow	m³/min	295	354	



### Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

### Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator			
Manufacturer		MARELLI	
Origin		ITALY	
Model		MJB315SA4	
No of Phase		3	
Power Factor		0,8	
No of Bearing		SINGLE	
No of Poles		4	
No of Leads		12	
Voltage Regulation ( Steady State)		± %0,5	
Insulation Class		H	
Degree of Protection		IP 23	
Excitation System		AVR (Automatic Voltage Regulator), Brushless	
Connection Type		STAR	
Total Harmonic Content (No Load)		< %2	
Frequency	Hz	50	60
Voltage Output	VAC	230 / 400	254 / 440
Rated Power (Standby)	kVA	330	385
Efficiency	%	93,1	93,4

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	1337 x 3969 x 1950	2940	510	TBA
Open Skid	1000 x 3000 x 1565	2230	380	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.  
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.  
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask    TBD: To Be Determined    NA: Not Available    N/A: Not Applicable

TTD330DW0508-EN

www.teksangenerator.com

