

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	34	39		
	kW	27	31		
Prime Power (PRP)	kVA	30	36		
	kW	24	29		



Engine					
Manufacturer		MITSUBISHI			
Origin		JAPAN			
Model		S4S-61SD			
No of Cylinder / Configuration		4 - INLINE			
Displacement		lt	3,331		
Bore / Stroke		mm	94 / 120		
Compression Ratio		22:1			
Aspiration		Naturally Aspirated			
Governor Type		MECHANIC			
Cooling System		WATER			
Coolant Capacity		lt	9,5		
Lubrication Oil Capacity		lt	9		
Electrical System		VDC	12		
Speed / Frequency			1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power		kWm	31,6	36,5	
Fuel Consumption	lt/h	110 %	9,9	10,5	
		100 %	8,2	9,8	
		75 %	6	7,4	
		50 %	4,2	5	
Exhaust Outlet Temperature		°C	500	530	
Exhaust Gas Flow		m³/min	6,75	7,5	
Combustion Air Flow		m³/min	2,47	2,8	
Cooling Air Flow		m³/min	13,95	15,5	



Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator					
Manufacturer		MARELLI			
Origin		ITALY			
Model		MJB160MB4			
No of Phase		3			
Power Factor		0,8			
No of Bearing		SINGLE			
No of Poles		4			
No of Leads		12			
Voltage Regulation (Steady State)		± %0,5			
Insulation Class		H			
Degree of Protection		IP 23			
Excitation System		AVR (Automatic Voltage Regulator), Brushless			
Connection Type		STAR			
Total Harmonic Content (No Load)		< %2			
Frequency		Hz	50	60	
Voltage Output		VAC	230 / 400	254 / 440	
Rated Power (Standby)		kVA	35,2	42,2	
Efficiency		%	88,3	88,3	

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	987 x 2265 x 1570	932	90	TBA
Open Skid	750 x 1600 x 1170	594	90	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask TBD: To Be Determined NA: Not Available N/A: Not Applicable

TTD34MS0508-EN

www.teksangenerator.com

