

Power Output Ratings		50 Hz / 400 V		60 Hz / 440 V	
Standby Power (ESP)	kVA	52	58		
	kW	41	47		
Prime Power (PRP)	kVA	47	53		
	kW	38	42		

**TBA**

Engine					
Manufacturer		LOVOL			
Origin		CHINA			
Model		1003TG			
No of Cylinder / Configuration		3 - INLINE			
Displacement		lt	2,99		
Bore / Stroke		mm	100 / 127		
Compression Ratio		17,5:1			
Aspiration		Turbocharged			
Governor Type		MECHANIC			
Cooling System		WATER			
Coolant Capacity		lt	17		
Lubrication Oil Capacity		lt	8,6		
Electrical System		VDC	12		
Speed / Frequency			1500 rpm / 50 Hz	1800 rpm / 60 Hz	
Engine Gross Power		kWm	48	55	
Fuel Consumption	lt/h	110 %	10	11,5	
		100 %	9	10	
		75 %	8,5	9	
		50 %	4,6	5,2	
Exhaust Outlet Temperature		°C	580	550	
Exhaust Gas Flow		m³/min	6,8	8,7	
Combustion Air Flow		m³/min	3,5	5	
Cooling Air Flow		m³/min	80	110	



### Standby Power



Standby power is defined as the maximum power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 500 hours of operation per year under average of 70% load. Overloading is not permissible.

### Prime Power

Prime power is defined as being the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hours.

Alternator					
Manufacturer		MARELLI			
Origin		ITALY			
Model		MJB200SB4			
No of Phase		3			
Power Factor		0,8			
No of Bearing		SINGLE			
No of Poles		4			
No of Leads		12			
Voltage Regulation ( Steady State)		± %0,5			
Insulation Class		H			
Degree of Protection		IP 23			
Excitation System		AVR (Automatic Voltage Regulator), Brushless			
Connection Type		STAR			
Total Harmonic Content (No Load)		< %2			
Frequency		Hz	50	60	
Voltage Output		VAC	230 / 400	254 / 440	
Rated Power (Standby)		kVA	53	65,5	
Efficiency		%	88,7	89,1	

	W x L x H (mm)	Weight (kg)	Fuel Tank (lt)	Noise (dBA)
Canopied	987 x 2265 x 1570	1136	90	TBA
Open Skid	750 x 1600 x 1170	835	90	TBA



- Technical information and values are according to ISO8528, ISO3046, NEMA MG-1.22, IEC 60034-1, BS 4999-5000, VDE 0530 standards.  
 - Producing with ISO9001, ISO14001, OHSAS18001, TSE, CE standards.  
 - All information given in this leaflet is intended for general purposes only. Due to a policy continuous improvement Teksan reserves the right to amend details and specifications without notice and all information given is subject to the Teksan's current condition of sales.

TBA: To Be Ask    TBD: To Be Determined    NA: Not Available    N/A: Not Applicable    TTD52PR0309-EN

